

THROWAWAY HOLDER SPECIFICATIONS

Holder Connection		Unit Weight		Overall Height (A)		Dimension Across Hex Flats				Dimension Across Inlet Corners (D)	
Inlet	Outlet	1,000# Assembly	3,000# Assembly	1,000# Assembly	3,000# Assembly	Inlet (B)		Outlet (C)		1,000# Assembly	3,000# Assembly
		lbs/ kgs	lbs/ kgs	in/ mm	in/ mm	1,000# Assembly	3,000# Assembly	1,000# Assembly	3,000# Assembly		
¼ MPT	¼ MPT	0.27/ 0,12	0.32/ 0,15	2.12/ 54	2.27/ 58	1 ½ in 28,6 mm	1 ¼ in 31,8 mm	1 in 25,4 mm	1 in 25,4 mm	1.30 in 33,0 mm	1.44 in 36,6 mm
¼ MPT	⅜ MPT	0.28/ 0,13	0.33/ 0,15	2.16/ 55	2.31/ 59						
¼ MPT	½ MPT	0.30/ 0,14	0.35/ 0,16	2.31/ 59	2.45/ 62						
¼ MPT	Muffled	0.25/ 0,11	0.30/ 0,14	1.81/ 46	1.95/ 50						
¼ MPT	Free	0.20/ 0,09	0.25/ 0,11	1.34/ 34	1.49/ 38						
⅜ MPT	⅜ MPT	0.29/ 0,13	0.34/ 0,15	2.19/ 56	2.34/ 59	1 ½ in 28,6 mm	1 ¼ in 31,8 mm	1 in 25,4 mm	1 in 25,4 mm	1.30 in 33,0 mm	1.44 in 36,6 mm
⅜ MPT	½ MPT	0.31/ 0,14	0.36/ 0,16	2.34/ 60	2.49/ 63						
⅜ MPT	Muffled	0.26/ 0,12	0.31/ 0,14	1.84/ 47	1.99/ 51						
⅜ MPT	Free	0.21/ 0,10	0.26/ 0,12	1.37/ 35	1.53/ 39						
½ MPT	½ MPT	0.34/ 0,15	0.39/ 0,18	2.50/ 63	2.50/ 64	1 ½ in 28,6 mm	1 ¼ in 31,8 mm	1 in 25,4 mm	1 in 25,4 mm	1.30 in 33,0 mm	1.44 in 36,6 mm
½ MPT	Muffled	0.29/ 0,13	0.34/ 0,15	2.00/ 51	2.01/ 51						
½ MPT	Free	0.24/ 0,11	0.29/ 0,13	1.53/ 39	1.54/ 39						
Holder Connection		Unit Weight 1,000# Assembly		Overall Height (A) 1,000# Assembly		Dimension Across Hex Flats				Dimension Across Inlet Corners (D)	
Inlet	Outlet	lbs	kgs	in/ mm		Inlet (B)		Outlet (C)			
¾ MPT	¾ MPT	0.37	0,17	2.51/ 63,8		1 ¼ in 31,8 mm		1 ½ in 28,6 mm		1.44 in 36,6 mm	
¾ MPT	Muffled	0.34	0,15	2.10/ 53,3							
¾ MPT	Free	0.29	0,13	1.73/ 43,9							
1 MPT	1 MPT	1.12	0,51	3.19/ 81,0		2 in 50,8 mm		2 in 50,8 mm		2.31 in 58,7 mm	
1 MPT	Muffled	1.24	0,56	2.50/ 63,5							
1 MPT	Free	1.12	0,51	2.25/ 57,2							

